Sicad Group

EUROCEL

PRODUCT INFORMATION

EUROCEL PVC 330

Short description:

Single sided packaging tape

Product Data

Backing:	0.033 mm PVC film
Adhesive:	natural rubber, white-brown- transparent
Total thickness	0.055 mm (white); 0.053 mm (brown); 0.052 mm (transparent)
Adhesion to steel	4,5 N/25mm
Tensile strength MD	112 N/25mm
Elongation at break	70 %
Temp. Resistance	60 °C

Application

Single sided carton sealing tape, suitable for use on standard and most recycled cartons; available in white, brown and transparent version.

Features	Benefits
Natural rubber adhesive	➢ Good adhesion in several applications ➢ Performing even at low temperature* ➢ Suitable for use on most recycled cartons **Suggested application at room temperature over 15°C before storing sealed items at lower temperature*
PVC backing	➢ Well adaptable to uneven shapes ➢ Good elongation ➢ No noise unwinding

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY
Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss